

# Operating Instructions for Variable area flow meter

Model: URB



### **URB**

# 1. Contents

2. Note 3   3. Instrument Inspection 3   4. Regulation Use 3   5. Operating Principle 4   6. Mechanical Connection 4   7. Operation 4   8. Maintenance 4   9. Technical Information 5   10. Order Codes 5   11. Dimensions 5   12. Disposal 6   13. EU Declaration of Conformance 7	1.	Contents	.2
4. Regulation Use 3   5. Operating Principle 4   6. Mechanical Connection 4   7. Operation 4   8. Maintenance 4   9. Technical Information 5   10. Order Codes 5   11. Dimensions 5   12. Disposal 6	2.	Note	.3
5. Operating Principle 4   6. Mechanical Connection 4   7. Operation 4   8. Maintenance 4   9. Technical Information 5   10. Order Codes 5   11. Dimensions 5   12. Disposal 6	3.	Instrument Inspection	.3
5. Operating Principle 4   6. Mechanical Connection 4   7. Operation 4   8. Maintenance 4   9. Technical Information 5   10. Order Codes 5   11. Dimensions 5   12. Disposal 6	4.	Regulation Use	.3
6. Mechanical Connection 4   7. Operation 4   8. Maintenance 4   9. Technical Information 5   10. Order Codes 5   11. Dimensions 5   12. Disposal 6	5.	Operating Principle	.4
8. Maintenance 4   9. Technical Information 5   10. Order Codes 5   11. Dimensions 5   12. Disposal 6	6.	Mechanical Connection	.4
8. Maintenance 4   9. Technical Information 5   10. Order Codes 5   11. Dimensions 5   12. Disposal 6	7.	Operation	.4
10. Order Codes511. Dimensions512. Disposal6			
11. Dimensions512. Disposal6	9.	Technical Information	.5
12. Disposal6	10.	Order Codes	.5
	11.	Dimensions	.5
	12.	Disposal	.6

#### Manufactured by:

Kobold-Unirota Ltd. 4400 Nyíregyháza Derkovits út 132-136. Tel.: +36-42-342-215 Fax: +36-42-500-175

E-Mail: <u>info.hu@kobold.com</u> Internet: <u>www.unirota.hu</u>

#### Sold by:

Kobold Messring GmbH Nordring 22-24 D-65719 Hofheim

Tel.: +49(0)6192-2990 Fax: +49(0)6192-23398 E-Mail: info.de@kobold.com Internet: www.kobold.com

page 2 URB K03/0323

#### 2. Note

Please read these operating instructions before unpacking and putting the unit into operation. Follow the instructions precisely as described herein.

The instruction manuals on our website <a href="www.kobold.com">www.kobold.com</a> are always for currently manufactured version of our products. Due to technical changes, the instruction manuals available online may not always correspond to the product version you have purchased. If you need an instruction manual that corresponds to the purchased product version, you can request it from us free of charge by email (<a href="mailto:info.de@kobold.com">info.de@kobold.com</a>) in PDF format, specifying the relevant invoice number and serial number. If you wish, the operating instructions can also be sent to you by post in paper form against an applicable postage fee.

Operating instructions, data sheet, approvals and further information via the QR code on the device or via <a href="https://www.kobold.com">www.kobold.com</a>

The devices are only to be used, maintained and serviced by persons familiar with these operating instructions and in accordance with local regulations applying to Health & Safety and prevention of accidents.

When used in machines, the measuring unit should be used only when the machines fulfil the EC-machine guidelines.

# 3. Instrument Inspection

Instruments are inspected before shipping and sent out in perfect condition. Should damage to a device be visible, we recommend a thorough inspection of the delivery packaging. In case of damage, please inform your parcel service / forwarding agent immediately, since they are responsible for damages during transit.

#### Scope of delivery:

The standard delivery includes:

Variable area flow meter model: URB

## 4. Regulation Use

Any use of the device, which exceeds the manufacturer's specification, may invalidate its warranty. Therefore, any resulting damage is not the responsibility of the manufacturer. The user assumes all risk for such usage.

Model K03/0323 page 3

# 5. Operating Principle

The Kobold URB model flowmeter/monitor works on the basis of the suspended float principle. It is used for measuring the flow rates in closed pipe line systems. The medium flows from below through a glass measuring cone that gets wider on top. Thus, the float is raised and indicates the respective flow rate on the scale provided on the measuring cone.

By its special design, this model is particularly suitable for applications where only very small operating pressures are available. Another advantage is offered by the very large sight glass which optically allows direct flow observation.

### 6. Mechanical Connection

#### **Before Installation:**

- Remove all transportation safety locks and ensure that no packing material remains within the unit.
- Be sure that the maximum allowable operating pressure and temperature is not exceeded (see Technical data).
- Install the flow meter in the piping system, ensure the instrument is under no mechanical stress/tension (install support bracing if necessary).
- Protect the measuring tube from external damage.
- Avoid pressure peaks in the measuring tube, e.g. from sudden surges or stoppage of flow.
- If possible, immediately after making mechanical connections, check whether the connections are properly sealed with no evidence of leakage

## 7. Operation

#### Overranging:

With non-pulsating flow, the maximum flow rate can be exceeded. Only an increase in pressure loss will result (max. permissible operating pressure must not be exceeded!)

## 8. Maintenance

If the medium to be measured is clean, the series URB is virtually maintenance-free. If deposits form on the inner housing or parts, periodic cleaning of the unit is recommended. Remove the units from the piping with a suitable tool; clean the flow meter with a suitable cleaning agent or make use of an ultrasonic bath.

page 4 URB K03/0323

# 9. Technical Information

Operating instructions, data sheet, approvals and further information via the QR code on the device or via <a href="https://www.kobold.com">www.kobold.com</a>

## 10. Order Codes

Operating instructions, data sheet, approvals and further information via the QR code on the device or via <a href="https://www.kobold.com">www.kobold.com</a>

## 11. Dimensions

Operating instructions, data sheet, approvals and further information via the QR code on the device or via <a href="https://www.kobold.com">www.kobold.com</a>

Model K03/0323 page 5


# 12. Disposal

#### Note!

- Avoid environmental damage caused by media-contaminated parts
- Dispose of the device and packaging in an environmentally friendly manner
- Comply with applicable national and international disposal regulations and environmental regulations.

#### **Batteries**

Batteries containing pollutants are marked with a sign consisting of a crossed-out garbage can and the chemical symbol (Cd, Hg, Li or Pb) of the heavy metal that is decisive for the classification as containing pollutants:



- 1. ,,Cd" stands for cadmium
- 2. "Hg" stands for mercury
- 3. "Pb" stands for lead
- 4. "Li" stands for lithium

#### **Electrical and electronic equipment**



page 6 URB K03/0323

# 13. EU Declaration of Conformance

We, KOBOLD Unirota Kft. Nyíregyháza Hungary, declare under our sole responsibility that the product:

Variable area flow meter Model: URB-...

to which this declaration relates is in conformity with the standards noted below:

**EN IEC 63000:2018** Technical documentation for the assessment of electrical and electronic products with respect to the restriction of hazardous substances

Also, the following EC guidelines are fulfilled:

**2011/65/EU RoHS** (category 9)

**2015/863/EU** Delegated Directive (RoHS III)

Nyíregyháza, 10 May 2022

Dénes Szabó General Manager

Model K03/0323 page 7